## 2025 RIDGE<sup>®</sup> XR CREW LIMITED HVAC





MSRP **\$38,099** 



**Ground Clearance** 

**Fuel Capacity** 

**Turning Radius** 

(LxWxH) Cargo Bed Load

Capacity Payload Capacity

Lighting

Frame

**Seating Capacity** 

**Towing Capacity** 

DETAILS

**Overall Length** 

**Overall Width** 

**Overall Height** 

**Curb Weight** 

**Estimated Dry Weight** 

**Cargo Bed Dimensions** 

METALLIC BLUISH GRAY

12.9 gal

19.0 ft

2,500 lb

161.1 in

64.0 in

82.3 in

All-LED lighting

34.6 x 49.0 x 12.8 in

1,000/600 lb CA Model

1,290/1,076 lb CA Model

5-person (2 row), bench seats

Ladder type, tubular steel

2,513.7/2,515.9 lb\*\* CA Model

2,624.0/2,626.2 lb\* CA Model



13.4/14.6 in (max preload); 13.4 in CA Model

## POWER

Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled
Displacement	999cc
Maximum Horsepower	116.0 hp <sup>1</sup> @ 8,500 rpm
Maximum Torque	73.8 lb-ft @ 8,000 rpm
Bore x Stroke	73.4 x 59.0mm
Compression Ratio	10.6:1
Fuel System	EFI
Ignition	TCBI with Digital Advance
Starting System	Electric
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 4WD with locking front/rear differential, shaft
Engine Braking	Yes
Alternator Output (max)	85 amp
Electronic Rider Aids	Power Modes, Economical Riding Indicator

## CAPABILITY

			_,,
Front Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Wheelbase	122.2 in
Rear Suspension / Wheel Travel	Long-Travel, Double Wishbone/12.7 in	Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery
Front Tires	Duro 30 x 10-14		voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) 8" Garmin Tread®, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full- color TFT Instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP Powersports, USB ports, KQR™ system compatible
Rear Tires	Duro 30 x 10-14		
Wheel Type	14" Aluminum	Additional Features	
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers	Color Choices	Metallic Bluish Gray





\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. Specifications subject to change. Visit Kawasaki.com for full product details.