

2025

RIDGE® XR DELUXE HVAC



MSRP

\$30,299

ICE GRAY

METALLIC GRAYSTONE



| POWER | |
|-------------------------|--|
| Engine | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled |
| Displacement | 999cc |
| Maximum Horsepower | 116.0 hp¹ @ 8,500 rpm |
| Maximum Torque | 73.8 lb-ft @ 8,000 rpm |
| Bore x Stroke | 73.4 x 59.0mm |
| Compression Ratio | 10.6:1 |
| Fuel System | EFI |
| Ignition | TCBI with Digital Advance |
| Starting System | Electric |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) |
| Final Drive | Selectable 4WD with locking front/rear differential, shaft |
| Engine Braking | Yes |
| Alternator Output (max) | 85 amp |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator |

| CAPABILITY | |
|---------------------------------|--|
| Front Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in |
| Rear Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in |
| Front Tires | Duro 30 x 10-14 |
| Rear Tires | Duro 30 x 10-14 |
| Wheel Type | 14" Aluminum |
| Steering | Rack-and-pinion w/ Electric Power Steering (EPS) |
| Front Brakes | Dual hydraulic 249mm discs with two-piston calipers |
| Rear Brakes | Dual hydraulic 249mm discs with single-piston calipers |

| | |
|------------------------------|--|
| Ground Clearance | 13.8/14.6 in (max preload); 13.8 in CA Model |
| Fuel Capacity | 12.9 gal |
| Turning Radius | 15.0 ft |
| Cargo Bed Dimensions (LxWxH) | 34.6 x 49.0 x 12.8 in |
| Cargo Bed Load Capacity | 1,000/600 lb CA Model |
| Payload Capacity | 1,275/875 lb CA Model |
| Seating Capacity | 3, bench seat |
| Towing Capacity | 2,500 lb |
| Lighting | All-LED lighting |

| DETAILS | |
|----------------------|---|
| Frame | Ladder type, tubular steel |
| Overall Length | 125.4 in |
| Overall Width | 64.0 in |
| Overall Height | 82.3 in |
| Estimated Dry Weight | 1,964.7/1,966.9 lb** CA Model |
| Curb Weight | 2,070.5/2,072.7 lb* CA Model |
| Wheelbase | 90.7 in |
| Instruments | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Additional Features | Full Cab with HVAC, Adjustable driver/passenger seats, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible |
| Color Choices | Ice Gray, Metallic Graystone |

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.