TERYX® KRX4™ 1000 LIFTED EDITION





\$27,999



LIME GREEN/SUPER BLACK



POWER

4-stroke, DOHC, 8-valve parallel-twin, liquid cooled **Engine**

Displacement 999cc

Maximum Torque 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio 11.5:1

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable

compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-

position adjustable compression damping/21.1 in

ITP Cryptid 32 x 10.00R15 6PR **Front Tires**

ITP Cryptid 32 x 10.00R15 6PR **Rear Tires**

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

Rear Brakes Dual hydraulic discs with single-piston calipers

Ground Clearance 14.8 in (max), 14.2 in (std)

Fuel Capacity 10.6 gal **Turning Radius**

Cargo Bed Dimensions

(LxWxH)

Cargo Bed Load

Capacity

Payload Capacity

Seating Capacity

Towing Capacity

Lighting

23.3 ft

14.6 x 33.1 x 9.1 in

351 lb

1,001 lb

N/A

(2) LED headlights, (2) LED taillights, LED stoplight

DETAILS

Ladder type, tubular steel

Overall Length 160.4 in **Overall Width** 68.1 in **Overall Height** 76.6 in

2,231.1 lb* / 2,233.3 lb* CA Model **Curb Weight**

Wheelbase 125 8 in

Multi-function digital meter with bar-style tachometer (2 Instruments display options), digital speedometer, bar-style fuel gauge,

gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning

lamp, and CVT belt warning lamp

Wheel Type

Additional Features Elevated snorkel intakes and CVT exhaust duct, Wide fender

flares, Front Bumper, F/R Tow Hooks, Steel skid-plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport Winch

Color Choices Lime Green/Super Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.