

2025

TERYX® KRX4™ 1000 LIFTED EDITION

Kawasaki

Let the Good Times Roll®

MSRP

\$27,999

LIME GREEN/SUPER BLACK



POWER		DETAILS	
Engine	4-stroke, DOHC, 8-valve parallel-twin, liquid cooled	Turning Radius	23.3 ft
Displacement	999cc	Cargo Bed Dimensions (LxWxH)	14.6 x 33.1 x 9.1 in
Maximum Torque	75.2 lb-ft @ 7,000 rpm	Cargo Bed Load Capacity	351 lb
Bore x Stroke	92.0 x 75.1mm	Payload Capacity	1,001 lb
Compression Ratio	11.5:1	Seating Capacity	4
Fuel System	DFI® with (2) 50mm throttle bodies	Towing Capacity	N/A
Ignition	TCBI with electronic advance	Lighting	(2) LED headlights, (2) LED taillights, LED sto­plight
Starting System	Electric	FRAME	
Transmission	Automatic CVT with centrifugal clutch (H,L,N,R)		
Final Drive	Selectable 2WD/4WD with locking front differential, shaft	Frame	Ladder type, tubular steel
Engine Braking	Yes	Overall Length	160.4 in
CAPABILITY		Overall Width	68.1 in
		Overall Height	76.6 in
Front Suspension / Wheel Travel	Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in	Curb Weight	2,231.1 lb* / 2,233.3 lb* CA Model
Rear Suspension / Wheel Travel	4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in	Wheelbase	125.8 in
Front Tires	ITP Cryptid 32 x 10.00R15 6PR	Instruments	Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, bar-style CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS warning lamp, and CVT belt warning lamp
Rear Tires	ITP Cryptid 32 x 10.00R15 6PR	Wheel Type	Alloy
Steering	Electric Power Steering (EPS) / rack-and-pinion	Additional Features	Elevated snorkel intakes and CVT exhaust duct, Wide fender flares, Front Bumper, F/R Tow Hooks, Skid plates w/ drain holes, Rear view mirror, WARN® VRX 45-S Powersport Winch
Front Brakes	Dual hydraulic discs with 2-piston calipers	Color Choices	Lime Green/Super Black
Rear Brakes	Dual hydraulic discs with single-piston calipers		
Ground Clearance	14.8 in (max), 14.2 in (std)		
Fuel Capacity	10.6 gal		

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.