2025

TERYX® S LE





\$15,499

ICE GRAY/SUPER BLACK



METALLIC MATTE TWILIGHT BLUE/SUPER BLACK



POWER

Engine 4-stroke, SOHC, 4-valve V-twin, liquid-cooled

Displacement 783cc

Maximum Torque 47.0 lb-ft @ 5,500 rpm

Bore x Stroke 85.0 x 69.0mm

Compression Ratio 10.7:1

DFI® with (2) 36mm Mikuni throttle bodies **Fuel System**

Ignition TCBI with Electronic Advance

Starting System Electric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Selectable 2WD/4WD with locking front differential, shaft **Final Drive**

Engine Braking

Ground Clearance 12.2 in (max) / 11.2 in (std)

Fuel Capacity 7.9 gal

Turning Radius 17.7 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load 600 lb Capacity

Payload Capacity 1,100 lb

Seating Capacity

Towing Capacity 1,300 lb

(4) LED headlights, (2) incandescent taillights, Lighting

27.6 x 43.3 x 10.4 in

incandescent stoplight

CAPABILITY

Front Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.7 in

Rear Suspension / **Wheel Travel**

Double wishbone, FOX 2.0 LSC Piggyback Shocks, fully adjustable preload, and adjustable compression

damping/10.0 in

Front Tires Maxxis® 27 x 9-14

Rear Tires Maxxis® 27 x 11-14

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes Dual hydraulic discs with 2-piston calipers

Sealed, oil-bathed, multi-disc Rear Brakes

DETAILS

Frame Steel Tube Double-X Reinforcement

Overall Length 118.1 in **Overall Width** 60.0 in

Overall Height 75.8 in

Curb Weight 1,570.0 lb* / 1,572.2 lb* CA Model

Wheelbase 88.2 in

Instruments Multi-function digital meter with speedometer, fuel gauge,

clock, hour meter, odometer, dual trip meter and parkingbrake indicator, R/N/P/4WD, water temp and low-oil-

pressure indicators

Alloy **Wheel Type**

Additional Features

Color Choices Ice Gray/Super Black, Metallic Matte Twilight Blue/Super

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.