

2025

# W230 ABS



MSRP  
**\$5,599**



METALLIC OCEAN BLUE/EBONY

## POWER

Engine	4-stroke, single-cylinder, SOHC, 2 valves, air-cooled
Displacement	233cc
Bore x Stroke	67.0 x 66.0mm
Compression Ratio	9.0:1
Maximum Torque	14.0 lb-ft @ 5,800 rpm
Fuel System	DFI® with 32mm throttle bodies
Ignition	TCBI with Digital Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Anti-lock Brake System

## PERFORMANCE

Front Suspension / Wheel Travel	37mm telescopic fork/4.6 in
Rear Suspension / Wheel Travel	Twin shocks with spring preload adjustability/3.7 in

Front Tire	90/90-18
Rear Tire	110/90-17
Front Brakes	Single 265mm disc with 2-piston calipers, ABS
Rear Brakes	Single 220mm disc with 1-piston caliper, ABS

## DETAILS

Frame Type	Semi-double cradle, steel
Rake/Trail	27.0°/3.7 in
Overall Length	83.6 in
Overall Width	31.4 in
Overall Height	42.9 in
Ground Clearance	5.9 in
Seat Height	29.3 in
Estimated Dry Weight	293.2 lb**
Curb Weight	315.2 lb*
Fuel Capacity	3.1 gal
Wheelbase	55.7 in
Color Choices	Metallic Ocean Blue/Ebony

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.