2025 **Z650**



THE APP

Black,



MSRP NON-ABS \$7,249



METALLIC SPARK BLACK/GREEN



METALLIC MATTE DARK GRAY/METALLIC SPARK BLACK

MSRP ABS \$7,749



Rear Tire 160/60-17 **POWER Front Brakes** Dual 300mm petal-style discs with two-piston calipers (and ABS) 4-stroke, 2-cylinder, DOHC, liquid-cooled Engine **Rear Brakes** Single 220mm petal-style disc (and ABS) Displacement 649cc **Bore x Stroke** 83.0 x 60.0mm DETAILS Compression 10.8:1 Ratio Trellis, high tensile steel Frame Type Maximum 67.0 hp1 @ 8,000 rpm 24.0°/3.9 in Rake/Trail Horsepower **Overall Length** 80.9 in **Maximum Torque** 48.5 lb-ft @ 6,700 rpm **Overall Width** 30.1 in **Fuel System** DFI® with Keihin 36mm throttle bodies **Overall Height** 41.9 in Ignition TCBI with Electronic Advance **Ground Clearance** 5.1 in Transmission 6-speed, return shift Seat Height 31.1 in **Final Drive** Sealed chain 381.5 lb** (ABS) / 379.3 lb** (non-ABS) 50-State **Estimated Dry Electronic Rider** Economical Riding Indicator, Kawasaki TRaction Weight Model Control (KTRC - 3 Modes), Anti-lock Brake System Aids (ABS) **Curb Weight** 414.5 lb* (ABS) / 412.3 lb* (non-ABS) 50-State Model **Fuel Capacity** 4.0 gal

PERFORMANCE

		11110000000	55.5 11
Front Suspension / Wheel Travel	41mm telescopic fork/4.9 in	Special Features	4.3" All-digital TFT color Instrumentation, Smartphone Connectivity via RIDEOLOGY
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable preload, swingarm/5.1 in	Color Choices	Metallic Matte Dark Gray/Metallic Spark B Metallic Spark Black/Green
Front Tire	120/70-17		

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Wheelbase

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

55 5 in

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features

