# **BRUTE FORCE® 450 4x4**





### **MSRP** \$6,899



**GRAYISH BLUE** 



FIRECRACKER RED



Electric

4.2 gal

10.2 ft

1,050 lb

225 lb

75/150 lb

taillight

Conventional tie-rod

#### **POWER**

**Engine** 4-stroke, single-cylinder, SOHC, liquid-cooled

Displacement 443cc

**Bore x Stroke** 89.0 x 71.2mm

**Compression Ratio** 

Maximum Horsepower 32.0 hp1 @ 7,000 rpm

**Maximum Torque** 

24.3 lb-ft @ 6,500 rpm

**Fuel System** 

FI with 38mm throttle body

Ignition

Digital DC-CDI

**Transmission** 

Automatic Continuously Variable Transmission (CVT) with

centrifugal clutch (H,L,N,R)

**Final Drive** 

Selectable 2WD/4WD with dual-mode differential, shaft

Dual A-arm, adjustable spring preload/7.6 in

## **DETAILS**

**Starting System** 

**Fuel Capacity** 

**Turning Radius** 

**Towing Capacity** 

Rack Capacity,

Front/Rear

Lighting

**Total Rack Capacity** 

Steering

**Frame Type** Double-cradle, high-tensile tubular steel

**Tread Width** 35.8/34.2 in

**Overall Length** 80.1 in **Overall Width** 

**Overall Height** 46.7 in

**Seat Height** 34.6 in

**Curb Weight** 683.4 lb\* / 685.6 lb\* CA Model

43.7 in

Wheelbase 47.8 in

Instruments Speedometer, tachometer, gear position indicator, fuel

gauge, clock, odometer, hour meter, trip meter,

LED headlights, LED handlebar mounted light, Halogen

Differential Lock/4WD indicator, etc.

**Special Features** KQR™ system-compatible front and rear cargo racks

**Color Choices** Grayish Blue, Firecracker Red

## CAPABILITY

Front Suspension /

Wheel Travel	
Rear Suspension / Wheel Travel	Dual A-arm, adjustable spring preload/7.9 in
Front Tire	AT 24 x 8-12
Rear Tire	AT 24 x 10-12
Front Brakes	Dual 202mm discs

Single 202mm disc

**Ground Clearance** 

**Rear Brakes** 

Scan with camera to view videos, key features and more.



9.3 in

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.