

2026

BRUTE FORCE® 450 4x4



Kawasaki
Let the Good Times Roll®

**MSRP
\$6,899**

- GRAYISH BLUE
- FIRECRACKER RED



POWER

Engine	4-stroke, single-cylinder, SOHC, liquid-cooled
Displacement	443cc
Bore x Stroke	89.0 x 71.2mm
Compression Ratio	9.1:1
Maximum Horsepower	32.0 hp ¹ @ 7,000 rpm
Maximum Torque	24.6 lb-ft @ 6,500 rpm
Fuel System	FI with 38mm throttle body
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R)
Final Drive	Selectable 2WD/4WD with dual-mode front differential, shaft

CAPABILITY

Front Suspension / Wheel Travel	Dual A-arm, adjustable spring preload/7.6 in
Rear Suspension / Wheel Travel	Dual A-arm, adjustable spring preload/7.9 in
Front Tire	AT 24 x 8-12
Rear Tire	AT 24 x 10-12
Front Brakes	Dual 202mm discs
Rear Brakes	Single 202mm disc
Ground Clearance	9.3 in
Starting System	Electric

Fuel Capacity	4.2 gal
Steering	Conventional tie-rod
Turning Radius	10.2 ft
Towing Capacity	1,050 lb
Total Rack Capacity	225 lb
Rack Capacity, Front/Rear	75/150 lb
Lighting	LED headlights, LED handlebar mounted light, Halogen taillight

DETAILS

Frame Type	Double-cradle, high-tensile tubular steel
Tread Width	35.8/34.2 in
Overall Length	80.1 in
Overall Width	43.3 in
Overall Height	46.7 in
Seat Height	34.6 in
Estimated Dry Weight	648.3 lb** / 650.5 lb** CA Model
Curb Weight	688.0 lb* / 690.2 lb* CA Model
Wheelbase	47.8 in
Instruments	Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, Differential Lock/4WD indicator, etc.
Special Features	KQR™ system-compatible front and rear cargo racks
Color Choices	Grayish Blue, Firecracker Red

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit Kawasaki.com for full product details.