## NEW 2026 BRUTE FORCE® 750 SE EPS





<sup>MSRP</sup> \$13,299



Steering

Rear

Lighting

DETAILS

Frame Type

**Tread Width** 

**Overall Length** 

**Overall Width** 

**Turning Radius** 

**Towing Capacity** 

**Total Rack Capacity** 

Rack Capacity, Front/

10.5 ft

1,250 lb

264.5 lb

88.0/176.0 lb

All-LED lighting

37.0/35.6 in

88.4 in

46.7 in

METALLIC GOLD SPARKLE DEEP GREEN



Rack-and-pinion w/ Electric Power Steering (EPS)

Double-cradle, high-tensile tubular steel

## POWER

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Maximum Horsepower	50.0 hp <sup>1</sup> @ 6,750 rpm
Maximum Torque	42.8 lb-ft @ 4,750 rpm
Fuel System	DFI® with two 34mm throttle bodies
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft

		Overall Height	47.8 in
CAPABILITY		Seat Height	35.2 in
Front Suspension /	Double wishbone, adjustable spring preload/6.9 in	Estimated Dry Weight	723.2 lb**
Wheel Travel		Curb Weight	769.5 lb*
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	Wheelbase	50.6 in
Front Tire	AT 25 x 8-12	Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h),
Rear Tire	AT 25 x 10-12	battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights	
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers		(engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	Special Features	WARN® VRX 25-S Powersport Winch, Front brush guard, Hand guards, Full-color TFT Instrumentation w/ Smartphone
Ground Clearance	8.7 in/9.6 in (max preload)		Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™
Starting System	Electric		system
Fuel Capacity	5.0 gal	Color Choices	Metallic Gold Sparkle Deep Green

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 'This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.