



NEW 2026

KLE® 500 SE ABS



MSRP
\$7,499

-  PEARL BLIZZARD WHITE
-  METALLIC BLUISH GREEN



POWER		Rear Tire	140/70-17
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled	Front Brakes	Single 300mm disc with 2-piston caliper and ABS
Displacement	451cc	Rear Brakes	Single 230mm disc with 2-piston caliper and ABS
Bore x Stroke	70.0 x 58.6mm	DETAILS	
Compression Ratio	11.3:1	Frame Type	Trellis, high tensile steel
Maximum Horsepower	51 hp ¹ @ 10,000 rpm	Rake/Trail	28.0° / 4.1 in
Maximum Torque	31.7 lb-ft @ 7,500 rpm	Overall Length	90.6 in
Fuel System	DFI® with 32mm throttle bodies	Overall Width	38.6 in
Ignition	TCBI with Electronic Advance	Overall Height	59.4 in (windscreen Hi) / 57.5 in (windscreen Lo)
Transmission	6-speed, return shift	Ground Clearance	7.3 in
Final Drive	Sealed chain	Seat Height	34.3 in
Electronic Rider Aids	Economical Riding Indicator, Selectable On/Off Anti-lock Brake System (ABS)	Estimated Dry Weight	385.9 lb** / 388.1 lb** 50-State Model
PERFORMANCE		Curb Weight	427.8 lb* / 430.0 lb* 50-State Model
Front Suspension / Wheel Travel	43mm inverted telescopic fork/8.3 in	Fuel Capacity	4.2 gal
Rear Suspension / Wheel Travel	Bottom-link Uni-Trak with adjustable spring preload/7.7 in	Wheelbase	61.2 in
Front Tire	90/90-21	Special Features	4.3-in All-digital TFT color Instrumentation, All-LED lighting, Tall adjustable windscreen, Handguards, Larger aluminum skid plate, ERGO-FIT®, Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE, USB Type-C outlet available as an accessory
		Color Choices	Pearl Blizzard White, Metallic Bluish Green

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.