

2026

KLX®110R L



MSRP
\$3,099

- LIME GREEN
- BRIGHT WHITE



| POWER | | Front Tire | |
|---------------------------------|--|------------------|--------------------------------------|
| Engine | 4-stroke, single-cylinder, SOHC, air-cooled | Rear Tire | 2.50 x 14 |
| Displacement | 112cc | Front Brakes | 3.00 x 12 |
| Bore x Stroke | 53.0 x 50.6mm | Rear Brakes | 90mm mechanical drum, cable actuated |
| Compression Ratio | 9.5:1 | | 110mm mechanical drum, rod actuated |
| Fuel System | Keihin PB18 carburetor and screw type throttle limiter on grip housing | DETAILS | |
| Ignition | DC-CDI | Frame Type | Backbone frame, high-tensile steel |
| Transmission | 4-speed, return shift, wet multi-disc manual clutch | Rake/Trail | 24.2° / 1.9 in |
| Final Drive | Chain | Overall Length | 61.4 in |
| PERFORMANCE | | Overall Width | 25.6 in |
| Front Suspension / Wheel Travel | 30mm hydraulic telescopic fork/5.5 in | Overall Height | 39.0 in |
| Rear Suspension / Wheel Travel | Swingarm with single hydraulic shock/5.2 in | Ground Clearance | 10.4 in |
| | | Seat Height | 28.7 in |
| | | Dry Weight | 158.7 lb** |
| | | Curb Weight | 167.5 lb* |
| | | Fuel Capacity | 1.0 gal |
| | | Wheelbase | 42.3 in |
| | | Color Choices | Lime Green, Bright White |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.