



2026

# KLX<sup>®</sup>140R F



MSRP  
**\$4,449**

-  LIME GREEN
-  BRIGHT WHITE



## POWER

Engine	4-stroke, single-cylinder, SOHC, air-cooled
Displacement	144cc
Bore x Stroke	58.0 x 54.4mm
Compression Ratio	9.5:1
Fuel System	Keihin PB20 carburetor
Ignition	Digital DC-CDI
Transmission	5-speed, return shift, with wet multi-disc manual clutch
Final Drive	Chain

Rear Tire	4.10 x 18
Front Brakes	Single 220mm petal disc with a dual-piston caliper
Rear Brakes	Single 186mm petal disc with single-piston caliper

## DETAILS

Frame Type	High-tensile steel, box-section perimeter
Rake/Trail	27.0° / 4.6 in
Overall Length	78.9 in
Overall Width	31.1 in
Overall Height	44.7 in
Ground Clearance	12.4 in
Seat Height	33.9 in
Estimated Dry Weight	205.0 lb**
Curb Weight	218.2 lb*
Fuel Capacity	1.5 gal
Wheelbase	52.4 in
Color Choices	Lime Green, Bright White

## PERFORMANCE

Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in
Rear Suspension / Wheel Travel	Uni-Trak <sup>®</sup> linkage system and single shock with piggyback reservoir, 20-way rebound damping and threaded preload adjustability/7.9 in
Front Tire	2.75 x 21

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.  
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.