2026 **KLX®140R F**







POWER Engine 4-stroke, single-cylinder, SOHC, air-cooled Displacement 144cc **Bore x Stroke** 58.0 x 54.4mm Compression 9.5:1 Ratio **Fuel System** Keihin PB20 carburetor Ignition **Digital DC-CDI** 5-speed, return shift, with wet multi-d Transmission manual clutch **Final Drive** Chain

PERFORMANCE

	Front Suspension / Wheel Travel	33mm telescopic fork/7.5 in	Seat Height	
			Estimated Dry Weight	
	Rear Suspension /	Uni-Trak® linkage system and single shock with piggyback reservoir, 20-way rebound	Curb Weight	
	Wheel Travel	damping and threaded preload adjustability/7.9 in	Fuel Capacity	
	Front Tire	2.75 x 21	Wheelbase	
			Color Choices	

Rear Tire	4.10 x 18	
Front Brakes	Single 220mm petal disc with a dual-piston caliper	
Rear Brakes	Brakes Single 186mm petal disc with single-piston caliper	

DETAILS

	Frame Type	High-tensile steel, box-section perimeter	
	Rake/Trail	27.0°/4.6 in	
lisc	Overall Length	78.9 in	
	Overall Width	31.1 in	
	Overall Height	44.7 in	
	Ground Clearance	12.4 in	
	Seat Height	33.9 in	
	Estimated Dry Weight	205.0 lb**	
shock ound	Curb Weight	218.2 lb*	
	Fuel Capacity	1.5 gal	
	Wheelbase	52.4 in	
	Color Choices	Lime Green, Bright White	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.