KLX[®]230 DF ABS





MSRP **\$5,999**



MEDIUM CLOUDY GRAY



POWER

Engine 4-stroke single, SOHC, air-cooled

9.4:1

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

17.0 hp¹ @ 8,000 rpm

Maximum Horsepower

Maximum Torque

13.3 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

PERFORMANCE

| Front Suspension / Wheel Travel | 37mm telescopic fork/7.9 in |
|------------------------------------|---|
| Rear Suspension / Wheel Travel | Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in |
| Front Tire | 2.75 x 21 |
| Rear Tire | 4.10 x 18 |

Specifications subject to change. Visit Kawasaki.com for full product details.

Front Brakes Single 265mm petal disc with a dual-piston caliper

Rear Brakes Single 220mm petal disc with single-piston

DETAILS

Frame Type High-tensile steel, perimeter

Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 36.2 in

Overall Height 45.3 in

Ground 9.4 in Clearance

Seat Height 33.3 in

3

Estimated Dry Weight

veigiii

284.4 lb**

Curb Weight 302.1 lb*

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features Ef

ERGO-FIT®, Aluminum skid plate, Engine guards, Hand guards, All-digital Instrumentation with

Smartphone Connectivity

Color Choices Medium Cloudy Gray

Scan with camera to view videos, key features and more.

