KLX[®]230 S





MSRP NON-ABS \$5,199

MSRP ABS \$5,499



LIME GREEN



BRIGHT WHITE



POWER

4-stroke single, SOHC, air-cooled **Engine**

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

9.4:1

Maximum Horsepower 17 hp1 @ 8,000 rpm

Maximum Torque

13.0 lb-ft @ 6,400 rpm

Fuel System

DFI® with 32mm throttle body

Ignition

TCBI with Electronic Advance

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

Aids

Anti-lock Brake System (ABS)

PERFORMANCE

Front Suspension 37mm telescopic fork/7.9 in / Wheel Travel **Rear Suspension /** Uni-Trak® linkage system and single shock with **Wheel Travel** adjustable spring preload/8.8 in **Front Tire** 2.75 x 21 **Rear Tire** 4.10 x 18

Specifications subject to change. Visit Kawasaki.com for full product details.

Front Brakes Single 240mm (265mm ABS Model) petal disc with a dual-piston caliper (and ABS)

Rear Brakes Single 220mm petal disc with single-piston caliper

(and ABS)

DETAILS

Frame Type Perimeter, high-tensile steel Rake/Trail 24.6°/3.8 in

Overall Length 81.9 in

Overall Width 33.3 in

Overall Height 44.9 in

Ground Clearance 9.4 in

Seat Height 33.3 in

Estimated Dry 277.7 lb** (ABS), 275.5 lb** (non-ABS) 50-State Weight Model; 275.6 lb** (ABS), 273.4 lb** (non-ABS) 49-

State Model

Curb Weight 293.3 lb* (ABS), 291.1 lb* (non-ABS) 50-State Model;

291.1 lb* (ABS), 288.9 lb* (non-ABS) 49-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP MOTORCYCLE

Color Choices Lime Green, Bright White

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied) 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.