²⁰²⁶ KLX[®]230R S







POWER		Front Brakes	Single 240mm petal disc with a dual-piston caliper
Engine	4-stroke, single-cylinder, SOHC, air-cooled	Rear Brakes	Single 220mm petal disc with single-piston caliper
Displacement	233cc		
Bore x Stroke	67.0 x 66.0mm	DETAILS	
Compression Ratio	9.4:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	DFI® with 32mm Keihin throttle body	Rake/Trail	24.6°/3.9 in
Ignition	TCBI with electronic advance	Overall Length	80.5 in
Transmission	6-speed, return shift with wet multi-disc	Overall Width	33.3 in
mansiinssion	manual clutch	Overall Height	46.7 in
Final Drive	Chain	Ground Clearance	10.6 in
PERFORMANCE		Seat Height	34.4 in
Front Suspension /	37mm telescopic fork/8.7 in	Estimated Dry Weight	247.0 lb** / 249.1 lb** 50-State Model
Wheel Travel		Curb Weight	262.4 lb* / 264.5 lb* 50-State Model
Rear Suspension /	Uni-Trak [®] linkage system and single shock with adjustable spring preload/8.8 in	Fuel Capacity	2.0 gal
Wheel Travel		Wheelbase	53.3 in
Front Tire	80/100-21	Color Choices	Lime Green, Bright White
Rear Tire	100/100-18		

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.