KLX®230SM ABS





MSRP **\$5,799**





POWER

Engine 4-stroke single, SOHC, air-cooled

9.4:1

Displacement 233cc

Bore x Stroke 67.0 x 66.0mm

Compression

Ratio

17 hp¹ @ 8,000 rpm

Maximum Horsepower

13.0 lb-ft @ 6,400 rpm

Maximum Torque

DFI® with 32mm throttle body

Fuel System
Ignition

TCBI with Electronic Advance

Anti-lock Brake System (ABS)

Transmission

6-speed

Final Drive

Sealed chain

Electronic Rider

tectronic kider

Aids

Rear Tire 120/70-17

Front Brakes Single 300mm petal disc with a dual-piston

caliper and ABS

Rear Brakes Single 220mm petal disc with single-piston

caliper and ABS

PERFORMANCE

Front Suspension 37
/ Wheel Travel

37mm telescopic fork/7.4 in

Rear Suspension / Wheel Travel

Uni-Trak® linkage system and single shock with adjustable spring preload/8.8 in

Front Tire 110/70-17

DETAILS

Frame Type Perimeter, high-tensile steel

Rake/Trail 24.9°/3.0 in

Overall Length 80.1 in

Overall Width 33.3 in

Overall Height 44.3 in

Ground Clearance 8.7 in

Seat Height 33.1 in

Estimated Dry 286.5 lb** 50-State Model; 284.4 lb** 49-State

Weight Model

Curb Weight 302.1 lb* 50-State Model; 299.9 lb* 49-State Model

Fuel Capacity 2.0 gal

Wheelbase 53.7 in

Special Features ERGO-FIT®, LCD Instrumentation with Smartphone

Connectivity via RIDEOLOGY THE APP

MOTORCYCLE

Color Choices Neon Green/Ebony

Scan with camera to view videos, key features and more.

