## KLX®300SM





**MSRP** \$6.049

**NEON GREEN/EBONY** 



BATTLE GRAY/EBONY



## **POWER**

**Engine** 4-stroke, single-cylinder, DOHC, liquid-cooled

**Displacement** 292cc

78.0 x 61.2mm

Compression

**Bore x Stroke** 

**Ratio** 

11.1:1

Maximum Horsepower

25.0 hp1 @ 8,000 rpm

**Maximum Torque** 

17.7 lb-ft @ 7,000 rpm

**Fuel System** 

DFI® with 34mm Keihin throttle body

Ignition

CDI

**Transmission** 

6-speed, return shift with wet multi-disc manual

43mm inverted cartridge fork with adjustable

Uni-Trak® gas charged shock with piggyback

reservoir with adjustable rebound damping and

compression damping/9.1 in

clutch

**Final Drive** Chain

**PERFORMANCE** 

**Front Suspension** 

**Rear Suspension** 

/ Wheel Travel

/ Wheel Travel

**Front Brakes** 

**Rear Tire** 

Single 300mm petal disc with a dual-piston

caliper

130/70-17

**Rear Brakes** 

**DETAILS** 

Single 240mm petal disc with single-piston

caliper

**Frame Type** Tubular, semi-double cradle

Rake/Trail

25.0°/2.8 in

**Overall Length** 

83.3 in

**Overall Width** 

31.1 in

**Overall Height** 

44.7 in

Ground Clearance 9.3 in

**Seat Height** 

33.9 in

**Estimated Dry** Weight

286.6 lb\*\*

**Curb Weight** 

304.3 lb\*

**Fuel Capacity** 

2.0 gal

Wheelbase

56.5 in

spring preload/8.1 in

Specifications subject to change. Visit Kawasaki.com for full product details.

**Color Choices** 

Neon Green/Ebony, Battle Gray/Ebony

**Front Tire** 

110/70-17



