

2026

KX™ 250



MSRP  
\$8,999



POWER		Front Tire	80/100-21
Engine	4-stroke, single-cylinder, DOHC, liquid-cooled	Rear Tire	110/90-19
Displacement	249cc	Front Brakes	Single semi-floating 270mm Braking petal disc with dual-piston caliper
Bore x Stroke	78.0 x 52.2mm	Rear Brakes	Single 240mm Braking petal disc with single-piston caliper
Compression Ratio	14.1:1	DETAILS	
Fuel System	DFI® with 44mm Keihin throttle body and dual injectors	Frame Type	Aluminum perimeter
Ignition	Digital DC-CDI	Rake/Trail	27.0° / 4.6 in
Transmission	5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation	Overall Length	86.2 in
Final Drive	Chain	Overall Width	32.3 in
Electronic Rider Aids	Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode	Overall Height	49.8 in
PERFORMANCE		Ground Clearance	13.4 in
Front Suspension / Wheel Travel	49mm Showa inverted telescopic coil-spring fork with 16-way compression and rebound damping / 12.0 in	Seat Height	37.6 in
Rear Suspension / Wheel Travel	Uni-Trak® with dual-range (4 turns high speed / 19-way low-speed) compression damping, 22-way rebound damping and adjustable preload / 12.1 in	Curb Weight	230.9 lb* without fuel / 240.8 lb*
		Fuel Capacity	1.64 gal
		Wheelbase	58.5 in
		Special Features	Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT®
		Color Choices	Lime Green

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.