

2026

KX™ 450



MSRP  
\$10,499



POWER

|                       |                                                                                         |
|-----------------------|-----------------------------------------------------------------------------------------|
| Engine                | 4-stroke, single-cylinder, DOHC, liquid-cooled                                          |
| Displacement          | 449cc                                                                                   |
| Bore x Stroke         | 96.0 x 62.1mm                                                                           |
| Compression Ratio     | 12.5:1                                                                                  |
| Fuel System           | DFI® with 44mm Keihin throttle body                                                     |
| Ignition              | Digital CDI with handlebar-controlled power modes                                       |
| Transmission          | 5-speed, return shift, with wet multi-disc manual clutch and hydraulic clutch actuation |
| Final Drive           | Chain                                                                                   |
| Electronic Rider Aids | Power Modes, Kawasaki TRaction Control (KTRC), Launch Control Mode                      |

PERFORMANCE

|                                 |                                                                                                                                                                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Front Suspension / Wheel Travel | 49mm Showa inverted telescopic coil-spring fork with 21-way adjustable compression and 22-way adjustable rebound damping/12.0 in                                                                                                    |
| Rear Suspension / Wheel Travel  | Uni-Trak® gas charged shock with piggyback reservoir with adjustable dual-range compression damping (19-way low speed and 4.25 turn stepless high speed), 23-way adjustable rebound damping and stepless adjustable preload/12.1 in |

|              |                                                                                                           |
|--------------|-----------------------------------------------------------------------------------------------------------|
| Front Tire   | 80/100-21                                                                                                 |
| Rear Tire    | 120/80-19                                                                                                 |
| Front Brakes | Single semi-floating 270mm Braking/Sunstar petal disc with Brembo master cylinder and dual-piston caliper |
| Rear Brakes  | Single 240mm Braking/Sunstar petal disc with single-piston caliper                                        |

DETAILS

|                  |                                                             |
|------------------|-------------------------------------------------------------|
| Frame Type       | Aluminum perimeter                                          |
| Rake/Trail       | 26.6° / 4.5 in                                              |
| Overall Length   | 85.8 in                                                     |
| Overall Width    | 32.3 in                                                     |
| Overall Height   | 50.0 in                                                     |
| Ground Clearance | 13.6 in                                                     |
| Seat Height      | 37.8 in                                                     |
| Curb Weight      | 238.3 lb* without fuel / 248.2 lb*                          |
| Fuel Capacity    | 1.64 gal                                                    |
| Wheelbase        | 58.3 in                                                     |
| Special Features | Smartphone Connectivity via RIDELOGY THE APP KX™, ERGO-FIT® |
| Color Choices    | Lime Green                                                  |

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.