2026 **KX**[™]65

Let the Good Times Rol





Rear Tire 80/100-12 **POWER Front Brakes** Single 180mm disc with single-piston caliper Engine 2-stroke, single-cylinder, liquid-cooled Single 180mm disc with single-piston **Rear Brakes** Displacement 64cc caliper **Bore x Stroke** 44.5 x 41.6mm **DETAILS** Compression 8.4:1 Ratio High-tensile steel semi-double cradle Frame Type **Fuel System** 24mm Mikuni carburetor Rake/Trail 27.0°/2.4 in Ignition CDI with digital advance **Overall Length** 62.6 in **Transmission** 6-speed, return shift, with wet multi-disc manual clutch **Overall Width** 29.9 in **Final Drive** Chain **Overall Height** 37.6 in Ground 12.0 in PERFORMANCE Clearance **Seat Height** 29.9 in 33mm leading axle telescopic fork with Front Suspension / 4-way rebound damping/8.3 in **Curb Weight** 126.1 lb* without fuel / 132.2 lb* Wheel Travel **Fuel Capacity** 1.0 gal Uni-Trak[®] single shock system with Rear Suspension / stepless 3-turns rebound damping and

Front Tire

Wheel Travel

60/100-14

fully adjustable spring preload/9.4 in

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

44.1 in

Lime Green

Wheelbase

Color Choices

Scan with camera to view videos. key features and more.

