

2026

MULE™ 4010 TRANS4x4®

Kawasaki

Let the Good Times Roll®



- MSRP
- \$14,249
- TIMBERLINE GREEN
- DARK ROYAL RED



POWER		REAR BRAKES	
Engine	4-stroke, 2-cylinder, OHV, 90° V-twin, Liquid-cooled	Park Brake Type	Drum
Displacement	617cc	Ground Clearance	Independent, mechanical drum
Maximum Horsepower	20.0 hp¹ @ 3,600 rpm	Fuel Capacity	7.1 in
Maximum Torque	34.7 lb-ft @ 2,500 rpm	Turning Radius	6.3 gal
Bore x Stroke	76.0 x 68.0mm	Cargo Bed Dimensions (LxWxH)	12.8 ft
Compression Ratio	10:3:1	Cargo Bed Load Capacity	50.4 x 47.6 x 11.2 in (2-person) / 30.3 x 47.6 x 11.2 in (4-person)
Fuel System	DFI® with 34mm Mikuni throttle body	Payload Capacity	800 lb (2-person) / 401 lb (4-person)
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Capacity	1,330 lb
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Towing Capacity	2-4
Engine Braking	No	Lighting	1,200 lb
Alternator Output (max)	23 amp		(2) Halogen headlights, (2) tail/brake lights
CAPABILITY		DETAILS	
Front Suspension / Wheel Travel	MacPherson Strut/3.9 in	Overall Length	128.5 in
Rear Suspension / Wheel Travel	DeDion Axle/2.8 in	Overall Width	58.5 in
Front Tires	23 x 11-10	Overall Height	75.8 in
Rear Tires	23 x 11-10	Estimated Dry Weight	1,521.5 lb**
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)	Curb Weight	1,587.6 lb*
Front Brakes	Drum	Wheelbase	85.2 in
		Instruments	Parking brake warning light, coolant temperature warning light, 12V DC outlet, fuel gauge, hour meter
		Color Choices	Timberline Green, Dark Royal Red

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ 4000/4010 and MULE 4000/4010 TRANS™ Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.