

2026

MULE PRO-FXT™ 1000 PLATINUM RANCH EDITION

Kawasaki

Let the Good Times Roll®



MSRP


\$22,499

 METALLIC DEEP RED



POWER		DETAILS	
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled, gas	Ground Clearance	12.6 in (max), 11.6 in (std)
Displacement	999cc	Fuel Capacity	7.9 gal
Maximum Horsepower	70.0 hp ¹ @ 6,500 rpm	Turning Radius	16.0 ft
Maximum Torque	61.5 lb-ft @ 4,500 rpm	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Bore x Stroke	92.0 x 75.1mm	Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Compression Ratio	10.1:1	Payload Capacity	1,466.3/1,162.0 lb CA Model
Fuel System	DFI® with 38mm throttle body	Seating Capacity	3-person (1 row), 6 person (2 row)
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Towing Capacity	2,000 lb
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Lighting	(4) LED headlights
Engine Braking	Yes	Overall Length	
Alternator Output (max)	90 amp		
CAPABILITY		Overall Width	
Front Suspension / Wheel Travel	Double wishbone/11.0 in	Overall Height	
Rear Suspension / Wheel Travel	Double wishbone/10.1 in	Estimated Dry Weight	
Front Tires	26 x 9-12, radial	Curb Weight	
Rear Tires	26 x 11-12, radial	Wheelbase	
Wheel Type	Alloy	Instruments	
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering		
Front Brakes	Dual disc, 2-piston caliper	Additional Features	
Rear Brakes	Dual disc, 1-piston caliper		
Park Brake Type	Independent, mechanical disc	Color Choices	
		Metallic Deep Red	

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.