

2026

MULE PRO-FXT™ 820 EPS

Kawasaki

Let the Good Times Roll®



MSRP

\$16,999

TIMBERLINE GREEN

DARK ROYAL RED



POWER		Park Brake Type	Independent, mechanical disc
Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas	Ground Clearance	10.2 in
Displacement	812cc	Fuel Capacity	7.9 gal
Maximum Torque	48.0 lb-ft @ 3,500 rpm	Turning Radius	16.0 ft
Bore x Stroke	72.0 x 66.5mm	Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person) / 22.0 x 53.7 x 11.0 in (6-person)
Compression Ratio	9.5:1	Cargo Bed Load Capacity	999 lb (3-person)/350 lb (6-person)/348 lb CA Model
Fuel System	DFI® with 34mm throttle body (3)	Payload Capacity	1,616.3/1,263.5 lb CA Model
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Seating Capacity	3-person (1 row), 6 person (2 row)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock	Towing Capacity	2,000 lb
Engine Braking	Yes	Lighting	(2) Halogen headlights
Alternator Output (max)	75 amp	DETAILS	
CAPABILITY		Overall Length	133.3 in
Front Suspension / Wheel Travel	Double wishbone/8.7 in	Overall Width	64.0 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 in (L)/8.7 in (R)	Overall Height	77.6 in
Front Tires	26 x 9-12, radial	Estimated Dry Weight	1,861.0/1,863.2 lb** CA Model
Rear Tires	26 x 11-12, radial	Curb Weight	1,949.2/1,951.4 lb* CA Model
Wheel Type	Steel	Wheelbase	92.3 in
Steering	Rack-and-pinion w/ Electric Power Steering (EPS), Tilt steering	Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT warning indicator, neutral, reverse and parking indicators, seatbelt reminder lamps
Front Brakes	Dual disc, 2-piston caliper	Color Choices	Timberline Green, Dark Royal Red
Rear Brakes	Dual disc, 1-piston caliper		

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).  
All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.  
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.