





# 2026 NINJA® 650

**Kawasaki**  
Let the Good Times Roll®



MSRP NON-ABS  
**\$7,599**

MSRP ABS  
**\$8,199**

-  LIME GREEN
-  METALLIC FLAT SPARK BLACK/METALLIC CARBON GRAY
-  METALLIC MATTE WHITISH SILVER/  
METALLIC FLAT SPARK BLACK
-  METALLIC YELLOWISH GREEN/METALLIC SPARK BLACK



## POWER

Engine	4-stroke, parallel twin, DOHC, 8-valve, liquid cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Horsepower	67.0 hp <sup>1</sup> @ 8,000 rpm
Maximum Torque	48.5 lb-ft @ 6,700 rpm
Fuel System	DFI® with dual 36mm Keihin throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS only)

## PERFORMANCE

Front Suspension / Wheel Travel	41mm hydraulic telescopic fork/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in
Front Tire	120/70 x 17
Rear Tire	160/60 x 17

Front Brakes	Dual 300mm petal-type discs and 2-piston calipers (and ABS)
Rear Brakes	Single 220mm petal-type disc and single-piston caliper (and ABS)

## DETAILS

Frame Type	Trellis, high-tensile steel
Rake/Trail	24.0° /3.9 in
Overall Length	80.9 in
Overall Width	29.1 in
Overall Height	45.1 in
Ground Clearance	5.1 in
Seat Height	31.1 in
Estimated Dry Weight	392.5 lb** (ABS), 390.3 lb** (non-ABS) 50-State Model; 390.3 lb** (ABS), 388.1 lb** (non-ABS) 49-State Model
Curb Weight	425.6 lb* (ABS), 423.4 lb* (non-ABS) 50-State Model; 423.4 lb* (ABS), 421.2 lb* (non-ABS) 49-State Model
Fuel Capacity	4.0 gal
Wheelbase	55.5 in
Color Choices	Lime Green, Metallic Flat Spark Black/Metallic Carbon Gray, Metallic Matte Whitish Silver/Metallic Flat Spark Black, Metallic Yellowish Green/Metallic Spark Black

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](http://Kawasaki.com) for full product details.