

2026

NINJA H2[®] ABS

Kawasaki

Let the Good Times Roll[®]



MSRP

\$34,400

 MIRROR COATED SPARK BLACK



POWER		Rear Suspension / Wheel Travel	
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Front Tire	120/70-17
Displacement	998cc	Rear Tire	200/55-17
Bore x Stroke	76.0 x 55.0mm	Front Brakes	Dual 330mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo Stylema [®] calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Compression Ratio	8.5:1	Rear Brakes	Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)
Maximum Horsepower	240 hp ¹ @ 11,500 rpm	DETAILS	
Maximum Torque	104.9 lb-ft @ 11,000 rpm	Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Fuel System	DFI [®] with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger	Rake/Trail	24.5° / 4.1 in
Ignition	TCBI with Digital Advance	Overall Length	82.1 in
Transmission	6-speed, return shift, dog-ring	Overall Width	30.3 in
Final Drive	Sealed chain	Overall Height	44.3 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper	Ground Clearance	5.1 in
PERFORMANCE		Seat Height	32.5 in
Front Suspension / Wheel Travel	43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in	Estimated Dry Weight	480.7 lb**
		Curb Weight	524.8 lb*
		Fuel Capacity	4.5 gal
		Wheelbase	57.3 in
		Special Features	Supercharged engine, All-digital TFT color Instrumentation, All-LED lighting, Highly Durable Paint, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Mirror Coated Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.