# NINJA H2® CARBON ABS





### **MSRP** \$38,100



MIRROR COATED MATTE SPARK BLACK/ CANDY FLAT BLAZED GREEN



#### **POWER**

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled **Engine** 

Displacement 998cc

76.0 x 55.0mm Bore x Stroke

**Compression Ratio** 8.5:1

**Maximum Horsepower** 240 hp1 @ 11,500 rpm

**Maximum Torque** 104.9 lb-ft @ 11,000 rpm

**Fuel System** DFI® with 50mm throttle bodies (4) with dual injection;

Kawasaki Supercharger

TCBI with Digital Advance Ignition

**Transmission** 6-speed, return shift, dog-ring

**Final Drive** Sealed chain

**Electronic Rider Aids** Economical Riding Indicator, Kawasaki Cornering Management

Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins

**Electronic Steering Damper** 

## **PERFORMANCE**

Front Suspension / Wheel Travel

43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Öhlins TTX36 gas-charged shock with piggyback reservoir, 24-way compression and rebound damping adjustability, 15-way spring preload adjustability, and top-

outspring/5.3 in

120/70-17 **Front Tire Rear Tire** 200/55-17

Front Brakes Dual 330mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)

Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

#### **DETAILS**

**Rear Brakes** 

Trellis, high-tensile steel, with swingarm mounting plate Frame Type

Rake/Trail 24.5° / 4.1 in **Overall Length** 82.1 in **Overall Width** 30.3 in

**Overall Height** 44.3 in **Ground Clearance** 5.1 in

**Seat Height** 32.5 in

**Estimated Dry Weight** 480.7 lb\*\*

**Curb Weight** 524.8 lb\*

**Fuel Capacity** 4.5 gal Wheelbase 57.3 in

**Special Features** 

**Color Choices** 

Supercharged engine, All-digital TFT color Instrumentation, All-LED lighting, Carbon fiber, Highly Durable Paint, Serial

number stamp, Smartphone Connectivity via RIDEOLOGY THE

Mirror Coated Matte Spark Black/Candy Flat Blazed Green

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.