NINJA H2® SX SE ABS





\$29,999



METALLIC BRILLIANT GOLDEN BLACK/METALLIC DIABLO BLACK



POWER

4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled **Engine**

Displacement 998cc

76.0 x 55.0mm Bore x Stroke

Compression Ratio 11.2:1

Maximum Horsepower 207.0 hp1 @ 10,000 rpm

Maximum Torque 101.0 lb-ft @ 8,500 rpm

DFI® with 40mm throttle bodies (4); Kawasaki Supercharger **Fuel System**

TCBI with Digital Advance Ignition

Transmission 6-speed, return shift, dog-ring

Final Drive Sealed chain

Electronic Rider Aids Economical Riding Indicator, Advanced Rider Assistance

Systems (ARAS): Forward Collision Warning (FCW), Blind-Spot Detection (BSD), Adaptive Cruise Control (ACC). Vehicle Hold Assist (VHA), Kawasaki Electronic Control Suspension with Showa Skyhook Technology (KECS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Anti-lock Brake System (ABS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (dual direction), IMU-Enhanced

Chassis Orientation Awareness

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted Showa fork with KECS-controlled rebound and compression damping, manual spring preload adjustability and top-out springs/4.7 in

Rear Suspension / Wheel Travel

Uni-Trak®, Showa BFRC lite gas-charged shock with piggyback reservoir, KECS-controlled compression and rebound damping electronically-adjustable spring preload/5.5 inspring/5.3 in

Front Tire 120/70-17

Rear Tire 190/55-17

Front Brakes Dual 320mm semi-floating discs with dual radial-mount,

opposed 4-piston Brembo Stylema® calipers, Kawasaki

Intelligent anti-lock Brake System (KIBS)

Rear Brakes Single 250mm disc with opposed 2-piston caliper, Kawasaki

Intelligent anti-lock Brake System (KIBS)

DETAILS

Frame Type Trellis, high-tensile steel, with swingarm mounting plate

Rake/Trail 24.7° / 4.1 in

Overall Length 85.6 in

Overall Width 31.1 in

Overall Height 49.6 in

Ground Clearance 5.1 in

Seat Height 32.9 in

Estimated Dry Weight 546.8 lb**

590.9 lb*

Curb Weight

Fuel Capacity 5.0 gal

Wheelbase 58.3 in

Special Features

Supercharged engine, 6.5" Full-color TFT Instrumentation, All-LED lighting including Cornering Lights, Kawasaki's Intelligent Proximity Activation Start System (KIPASS), Highly Durable Paint, Grip heaters, Tire Pressure Monitoring System (TPMS), Smartphone Connectivity via Kawasaki SPIN infotainment app

Color Choices

Metallic Brilliant Golden Black/Metallic Diablo Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). ¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of

drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.