

2026

NINJA H2®R ABS


Kawasaki

Let the Good Times Roll®



MSRP


\$59,100

 MIRROR COATED MATTE SPARK BLACK



POWER		REAR SUSPENSION / WHEEL TRAVEL	
Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled	Front Tire	120/60-17 V01F slick
Displacement	998cc	Rear Tire	190/65-17 V01R slick
Bore x Stroke	76.0 x 55.0mm	Front Brakes	Dual 330mm semi-floating discs with dual radial-mount, opposed 4-piston Brembo M50 Monobloc calipers, Kawasaki Intelligent anti-lock Brake System (KIBS)
Compression Ratio	8.3:1	Rear Brakes	Single 250mm disc with opposed 2-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS)
Maximum Horsepower	322 hp ¹ @ 14,000 rpm	DETAILS	
Maximum Torque	121.5 lb-ft @ 12,500 rpm	Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Fuel System	DFI® with 50mm throttle bodies (4) with dual injection; Kawasaki Supercharger	Rake/Trail	25.1° / 4.3 in
Ignition	TCBI with Digital Advance	Overall Length	81.5 in
Transmission	6-speed, return shift, dog-ring	Overall Width	33.5 in
Final Drive	Sealed chain	Overall Height	45.7 in
Electronic Rider Aids	Economical Riding Indicator, Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), IMU-Enhanced Chassis Orientation Awareness, Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control (KEBC), Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper	Ground Clearance	5.1 in
PERFORMANCE		Seat Height	32.7 in
Front Suspension / Wheel Travel	43mm inverted Kayaba AOS-II fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in	Estimated Dry Weight	432.2 lb**
		Curb Weight	476.3 lb*
		Fuel Capacity	4.5 gal
		Wheelbase	57.1 in
		Special Features	Supercharged engine, Carbon fiber aerodynamic downforce generating devices, Highly Durable Paint
		Color Choices	Mirror Coated Matte Spark Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.