

NEW 2026

# NINJA® ZX™-10RR ABS



MSRP  
**\$29,999**



LIME GREEN

## POWER

Engine	4-stroke, in-line 4-cylinder, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Maximum Horsepower	190.0 hp <sup>1</sup> @ 11,500 rpm
Maximum Torque	82.5 lb-ft @ 11,300 rpm
Fuel System	DFI® with 47mm throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Anti-lock Brake System (ABS) (ABS only), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

## PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Showa Balance Free Fork (BFF) with external compression chamber, rebound and compression damping, spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with Showa Balance Free Rear Cushion (BFR) lite gas-charged shock with piggyback reservoir, rebound and compression damping, spring preload adjustability/4.2 in

Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Dual 330mm semi-floating Brembo discs with radial-mount 4-piston Brembo M50 monobloc calipers (and ABS)
Rear Brakes	Single 220mm disc with aluminum single-piston caliper (and ABS)

## DETAILS

Frame Type	Twin spar, cast aluminum
Rake/Trail	25.0° / 4.1 in
Overall Length	82.1 in
Overall Width	29.5 in
Overall Height	46.5 in
Ground Clearance	5.1 in
Seat Height	32.5 in
Estimated Dry Weight	421.2 lb**
Curb Weight	458.6 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in
Special Features	5" All-digital TFT color instrumentation, All-LED lighting, Öhlins steering damper, Smartphone Connectivity with available Voice Command and Turn-by-Turn Navigation via RIDEOLOGY THE APP MOTORCYCLE***
Color Choices	Lime Green

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*\*RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

**Kawasaki**  
Let the Good Times Roll®