

UPDATED 2026

RIDGE® CREW PLATINUM RANCH EDITION HVAC



MSRP

\$37,199

 METALLIC DEEP RED/EBONY



| POWER | | DETAILS | |
|---------------------------------|--|------------------------------|--|
| Engine | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled | Fuel Capacity | 12.9 gal |
| Displacement | 999cc | Turning Radius | 19.0 ft |
| Maximum Horsepower | 116.0 hp ¹ @ 8,500 rpm | Cargo Bed Dimensions (LxWxH) | 34.6 x 49.0 x 12.8 in |
| Maximum Torque | 73.8 lb-ft @ 8,000 rpm | Cargo Bed Load Capacity | 1,000/600 lb CA Model |
| Bore x Stroke | 73.4 x 59.0mm | Payload Capacity | 1,290 lb |
| Compression Ratio | 10.6:1 | Seating Capacity | 6-person (2 row), bench seats |
| Fuel System | EFI | Towing Capacity | 2,500 lb |
| Ignition | TCBI with Digital Advance | Lighting | All-LED lighting |
| Starting System | Electric | | |
| Transmission | Continuously Variable Transmission (CVT) with (H,L,N,R) | | |
| Final Drive | Selectable 4WD with locking front/rear differential, shaft | Frame | Ladder type, tubular steel |
| Engine Braking | Yes | Overall Length | 157.9 in |
| Alternator Output (max) | 85 amp | Overall Width | 64.0 in |
| Electronic Rider Aids | Power Modes, Economical Riding Indicator | Overall Height | 82.3 in |
| | | Estimated Dry Weight | 2,443.1/2,445.3 lb** CA Model |
| | | Curb Weight | 2,553.4/2,555.6 lb* CA Model |
| | | Wheelbase | 122.2 in |
| | | Instruments | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| | | Additional Features | 8-in Garmin Tread®, (4) 6.5-in speakers, Front/rear cameras, WARN® VRX 45-S Powersport Winch, Full Cab with HVAC, Adjustable driver's seat, Front stabilizer bar, ERGO-FIT®, Full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible |
| | | Color Choices | Metallic Deep Red/Ebony |
| CAPABILITY | | | |
| Front Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in | | |
| Rear Suspension / Wheel Travel | Long-Travel, Double Wishbone/12.7 in | | |
| Front Tires | SUNF 30 x 10-14 | | |
| Rear Tires | SUNF 30 x 10-14 | | |
| Wheel Type | 14" Aluminum | | |
| Steering | Rack-and-pinion w/ Electric Power Steering (EPS) | | |
| Front Brakes | Dual hydraulic 249mm discs with two-piston calipers | | |
| Rear Brakes | Dual hydraulic 249mm discs with single-piston calipers | | |
| Ground Clearance | 13.4/14.6 in (max preload); 13.4 in CA Model | | |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.