TERYX KRX® 1000 BLACKOUT EDITION





\$26,399



FLAT EBONY



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes **DETAILS**

Lighting

Frame

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Ladder type, tubular steel

Overall Length 133.3 in **Overall Width** 68.1 in **Overall Height** 76.0 in

Estimated Dry Weight 1,931.6 lb** / 1,933.8 lb** CA Model 2,030.8 lb* / 2,033.0 lb* CA Model **Curb Weight**

20.3 ft

351 lb

781 lb

2

N/A

14.6 x 33.1 x 9.1 in

Wheelbase

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip

meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

(2) LED headlights, (2) LED taillights, LED stoplight, (4) LED light bars

warning lamp, and CVT belt warning lamp

Additional Features LED light bars (38-in mounted to front of roof, 8-in mounted to front bumper, (2) 8-in mounted to rear of roof), Front Bumper, Rear

Bumper, Steel skid-plates w/ drain holes, KQR™ Premium Roof, Hifonics® Audio System, WARN® VRX 45 Powersport Winch

Color Choices Flat Ebony

CAPABILITY

Front Suspension / Wheel Travel

Double wishbone, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/18.6 in

Rear Suspension / Wheel Travel

Steering

4-link trailing-arm rear suspension, FOX 2.5 PODIUM LSC shocks with piggyback reservoir, fully adjustable preload, and 24-position adjustable compression damping/21.1 in

Front Tires Maxxis® Carnivore 31 x 10.00R15 8PR **Rear Tires**

Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

258mm dual hydraulic discs with single-piston calipers

14.0 in (max), 13.4 in (std) **Ground Clearance**

Fuel Capacity 10.6 gal

Scan with camera to view videos. key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.