TERYX KRX® 1000 eS





\$24,799



SKY BLUE/SUPER BLACK



POWER

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with (2) 50mm throttle bodies **Fuel System**

Ignition TCBI with electronic advance

Starting System Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with locking front differential, shaft

Engine Braking Yes

DETAILS

Lighting

Turning Radius

Cargo Bed Load

Payload Capacity

Seating Capacity

Towing Capacity

(LxWxH)

Capacity

Cargo Bed Dimensions

Frame Ladder type, tubular steel

20.3 ft

351 lb

781 lb

2

N/A

14.6 x 33.1 x 9.1 in

Overall Length 132.1 in **Overall Width** 68.1 in **Overall Height** 77 0 in

Estimated Dry Weight 1,839.0 lb** / 1,841.2 lb** CA Model **Curb Weight** 1.938.2 lb* / 1.940.4 lb* CA Model

Wheelbase

Multi-function digital meter with bar-style tachometer (2 display Instruments

options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

(2) LED headlights, (2) LED taillights, LED stoplight

Wheel Type Alloy with bead-lock wheels

KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, **Additional Features**

TFT Full-Color Instrumentation with Smartphone Connectivity

Color Choices Sky Blue/Super Black

CAPABILITY

Front Suspension /

Wheel Travel

Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS

controlled compression damping/18.6 in

Rear Suspension / Wheel Travel

4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Internal Bypass shocks with piggyback reservoir, fully adjustable preload, and KECS controlled compression damping/21.1 in

Maxxis® Carnivore 31 x 10.00R15 8PR

Front Tires Rear Tires

Maxxis® Carnivore 31 x 10.00R15 8PR

Steering

Electric Power Steering (EPS) / rack-and-pinion

Front Brakes

258mm dual hydraulic discs with 2-piston calipers

Rear Brakes

258mm dual hydraulic discs with single-piston calipers

Ground Clearance Fuel Capacity

10.6 gal

14.4 in (max), 14.0 in (std)

Scan with camera to view videos. key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). **Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.