## TERYX KRX® 1000 eS





\$24,799



SKY BLUE/SUPER BLACK



## **POWER**

Engine 4-stroke, DOHC, 8-valve parallel-twin, liquid cooled

Displacement

Maximum Horsepower 110.0 hp1 @ 8,500 rpm **Maximum Torque** 75.2 lb-ft @ 7,000 rpm

Bore x Stroke 92.0 x 75.1mm

Compression Ratio

DFI® with (2) 50mm throttle bodies **Fuel System** 

Ignition TCBI with electronic advance

**Starting System** Flectric

Transmission Automatic CVT with centrifugal clutch (H,L,N,R)

**Final Drive** Selectable 2WD/4WD with locking front differential, shaft

**Engine Braking** Yes **Turning Radius** 20.3 ft

**Cargo Bed Dimensions** 14.6 x 33.1 x 9.1 in (LxWxH)

351 lb

Cargo Bed Load Capacity

**Payload Capacity** 781 lb

2 **Seating Capacity** 

**Towing Capacity** N/A

Lighting (2) LED headlights, (2) LED taillights, LED stoplight

## **CAPABILITY**

Front Suspension / Double wishbone, FOX 2.5 Podium Live Valve Internal Bypass shocks Wheel Travel with piggyback reservoir, fully adjustable preload, and KECS

controlled compression damping/18.6 in

Rear Suspension / 4-link trailing-arm rear suspension, FOX 2.5 Podium Live Valve Wheel Travel Internal Bypass shocks with piggyback reservoir, fully adjustable

Maxxis® Carnivore 31 x 10.00R15 8PR

preload, and KECS controlled compression damping/21.1 in

**Front Tires** Maxxis® Carnivore 31 x 10.00R15 8PR

Electric Power Steering (EPS) / rack-and-pinion Steering

Front Brakes 258mm dual hydraulic discs with 2-piston calipers

**Rear Brakes** 258mm dual hydraulic discs with single-piston calipers

14.4 in (max), 14.0 in (std) **Ground Clearance** 

**Fuel Capacity** 10.6 gal

**DETAILS** 

**Curb Weight** 

Frame

Ladder type, tubular steel

1.938.2 lb\* / 1.940.4 lb\* CA Model

**Overall Length** 132.1 in

**Overall Width** 68.1 in **Overall Height** 77 0 in

**Estimated Dry Weight** 1,839.0 lb\*\* / 1,841.2 lb\*\* CA Model

Wheelbase

Instruments

Multi-function digital meter with bar-style tachometer (2 display options), digital speedometer, bar-style fuel gauge, gear indicator (L, H, N, R), Power Mode, driving mode (2WD/4WD+Diff Lock) indicator, Economical Riding Indicator, clock, odometer, dual trip meters, hour meter, water temperature, digital battery gauge, barstyle CTV temperature, seatbelt warning lamp, oil warning lamp, engine check lamp, water temperature warning lamp, neutral indicator lamp, reverse indicator lamp, parking indicator lamp, EPS

warning lamp, and CVT belt warning lamp

**Additional Features** KQR™ Sport Roof, Front Bumper, Steel skid-plates w/ drain holes, TFT Full-Color Instrumentation with Smartphone Connectivity

**Color Choices** 

Sky Blue/Super Black

Scan with camera to view videos. key features and more.

**Rear Tires** 



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). \*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). 1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: The Teryx® side x side can be hazardous to operate. For your safety: Always wear a helmet, eye protection and protective clothing. Never operate under the influence of drugs or alcohol. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Protect the environment. The Kawasaki Teryx side x side is an off-highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. ©2025 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.