

2026

VERSYS® 650 LT ABS



MSRP
\$10,399



METALLIC DEEP BLUE/METALLIC SPARK BLACK

POWER

Engine	4-stroke, 2-cylinder, DOHC, 8 valves, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Horsepower	66.0 hp ¹ @ 8,500 rpm
Maximum Torque	45.0 lb-ft @ 7,000 rpm
Fuel System	DFI® with 38mm Keihin throttle bodies (2)
Ignition	TCBI with Electronic Advance
Transmission	6-speed with positive neutral finder
Final Drive	Sealed chain
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Economical Riding Indicator

PERFORMANCE

Front Suspension / Wheel Travel	41mm telescopic fork with stepless adjustable rebound and spring preload/5.9 in
Rear Suspension / Wheel Travel	Single offset laydown shock with remote adjustable spring preload/5.7 in
Front Tire	120/70 ZR-17

Rear Tire	160/60 ZR-17
Front Brakes	Dual 300mm petal-style discs with 2-piston calipers, ABS
Rear Brakes	Single 250mm petal-style disc with single-piston caliper, ABS

DETAILS

Frame Type	Double pipe diamond frame constructed from high-tensile steel
Rake/Trail	25° / 4.3 in
Overall Length	85.2 in
Overall Width	33.1 in
Overall Height	53.5 in/55.9 in (windshield down/up)
Ground Clearance	6.7 in
Seat Height	33.3 in
Estimated Dry Weight	444.1 lb** (+ approx. 20 lb** w/ saddlebags & hand guards)
Curb Weight	482.9 lb* (+ approx. 20 lb* w/ saddlebags & hand guards)
Fuel Capacity	5.5 gal
Wheelbase	55.7 in
Special Features	TFT color instrumentation with Smartphone Connectivity via RIDEOLOGY THE APP, Clean-mount hard saddlebag system, featuring KQR™ mounts
Color Choices	Metallic Deep Blue/Metallic Spark Black

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Kawasaki
Let the Good Times Roll®