

NEW 2026

Z650 S ABS

Kawasaki
Let the Good Times Roll®



MSRP
\$7,699



METALLIC MATTE GRAPHENE STEEL GRAY/
METALLIC FLAT SPARK BLACK



POWER

| | |
|------------------------------|---|
| Engine | 4-stroke, 2-cylinder, DOHC, liquid-cooled |
| Displacement | 649cc |
| Bore x Stroke | 83.0 x 60.0mm |
| Compression Ratio | 10.8:1 |
| Maximum Horsepower | 67.0 hp ¹ @ 8,000 rpm |
| Maximum Torque | 47.2 lb-ft @ 6,700 rpm |
| Fuel System | DFI® with Keihin 36mm throttle bodies |
| Ignition | TCBI with Electronic Advance |
| Transmission | 6-speed, return shift |
| Final Drive | Sealed chain |
| Electronic Rider Aids | Economical Riding Indicator, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) available as an accessory |

PERFORMANCE

| | |
|--|---|
| Front Suspension / Wheel Travel | 41mm inverted telescopic fork/4.9 in |
| Rear Suspension / Wheel Travel | Horizontal back-link with adjustable preload, swingarm/5.1 in |
| Front Tire | 120/70-17 |

| | |
|---------------------|---|
| Rear Tire | 160/60-17 |
| Front Brakes | Dual 300mm petal-style discs with two-piston calipers (and ABS) |
| Rear Brakes | Single 220mm petal-style disc (and ABS) |

DETAILS

| | |
|-----------------------------|---|
| Frame Type | Trellis, high tensile steel |
| Rake/Trail | 24.0° / 3.9 in |
| Overall Length | 80.9 in |
| Overall Width | 31.7 in |
| Overall Height | 42.5 in |
| Ground Clearance | 5.1 in |
| Seat Height | 31.7 in |
| Estimated Dry Weight | 374.9 lb** / 377.1 lb** 50-State Model |
| Curb Weight | 416.7 lb* / 419.0 lb* 50-State Model |
| Fuel Capacity | 4.0 gal |
| Wheelbase | 55.5 in |
| Special Features | 4.3-in All-digital TFT color Instrumentation, All-LED lighting, Smartphone Connectivity via RIDEOLOGY THE APP MOTORCYCLE, USB Type-C outlet available as an accessory |
| Color Choices | Metallic Matte Graphenesteel Gray/Metallic Flat Spark Black |

Scan with camera
to view videos,
key features
and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.