NEW 2026

Z900RS SE ABS





\$14,599



METALLIC SPARK BLACK



POWER

Engine 4-stroke, 4-cylinder, DOHC, 16-valve, liquid-cooled

DFI® with 36mm throttle bodies

Displacement 948cc

Bore x Stroke 73.4 x 56.0mm

Compression Ratio 11.8:1

Maximum 115.0 hp1 @ 9,300 rpm Horsepower

Maximum Torque

Fuel System

Ignition

Final Drive

73.0 lb-ft @ 7,700 rpm

TCBI with Electronic Advance

Sealed chain

Transmission 6-speed, return shift

Electronic Rider Aids

Economical Riding Indicator, Electronic Cruise Control, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Power Modes, Kawasaki Cornering Management Function (KCMF), Kawasaki Quick Shifter (KQS), IMU-Enhanced Chassis Orientation Awareness

PERFORMANCE

Front Suspension / **Wheel Travel**

41mm inverted telescopic fork with (12-way) adjustable compression and rebound (10-way) damping, spring preload (15-turn)/4.7

Rear Suspension / **Wheel Travel**

Horizontal back-link swingarm, Öhlins S46 shock with 30-position adjustable rebound damping and stepless

Specifications subject to change. Visit Kawasaki.com for full product details.

spring preload adjustability/5.5 in

Front Tire 120/70-17

Rear Tire 180/55-17

Front Brakes Dual 300mm discs with Brembo M4.32 monobloc four-

piston calipers and ABS

Trellis, high tensile steel

Rear Brakes Single 250mm disc with single-piston caliper and ABS

DETAILS

Frame Type

Rake/Trail 25.0°/3.9 in **Overall Length** 82 7 in **Overall Width** 32.1 in **Overall Height** 44.7 in **Ground Clearance** 5.5 in

Seat Height 32.3 in

Estimated Dry 434.4 lb**

Weight

Curb Weight 476.3 lb* **Fuel Capacity** 4.5 gal

Wheelbase

Special Features All-LED lighting, USB-C outlet, ERGO-FIT®, Smartphone Connectivity with available Voice Command and Turn-

by-Turn Navigation via RIDEOLOGY THE APP

MOTORCYCLE***

57.7 in

Color Choices Metallic Spark Black

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). *RIDEOLOGY THE APP and all trademarks, registered trademarks, logos, and copyrights are the property of their respective owners. Voice command and navigation functions will be available only to users who have purchased a license for those functions. Feature availability may vary to meet individual markets.

1This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard. KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.