

2027

KLR® 650 ADVENTURE ABS

Kawasaki

Let the Good Times Roll®



- BASE MSRP ABS
- \$8,199*
- CYPHER CAMO BEIGE/PEARL MATTE SAND KHAKI

BASE MSRP \$8,299[†] ABS
- METALLIC BLUISH GREEN

BASE MSRP \$8,199[†] ABS

POWER		Rear Tire	130/80-17
Engine	4-stroke, single cylinder, DOHC	Front Brakes	Single 300mm disc with 2-piston caliper and ABS
Displacement	652cc	Rear Brakes	Single 240mm disc with 2-piston caliper and ABS
Bore x Stroke	100.0 x 83.0mm	DETAILS	
Compression Ratio	9.8:1	Frame Type	Tubular, semi-double cradle
Maximum Horsepower	40 hp ¹ @ 6,000 rpm	Rake/Trail	30.0° / 4.8 in
Maximum Torque	39.1 lb-ft @ 4,500 rpm	Overall Length	89.8 in
Fuel System	DFI® with 40mm throttle body	Overall Width	38.2 in
Ignition	CDI	Overall Height	57.3/55.9 in (screen hi/lo)
Transmission	5-speed, return shift with wet multi-disc manual clutch	Ground Clearance	8.3 in
Final Drive	Sealed chain	Seat Height	34.3 in
Electronic Rider Aids	Anti-lock Brake System (ABS)	Estimated Dry Weight	443.0 lb**
PERFORMANCE		Curb Weight	487.1 lb*
Front Suspension / Wheel Travel	41mm telescopic fork/7.9 in	Fuel Capacity	6.1 gal
Rear Suspension / Wheel Travel	Uni-Trak® single shock with adjustable rebound damping and adjustable spring preload/8.0 in	Wheelbase	60.6 in
Front Tire	90/90-21	Special Features	All-digital multi-function instrumentation, Adjustable windscreen, Hand guards, Rear carrier, Fog lights, Frame sliders, Tank pad, Hard saddlebags
		Color Choices	Cypher Camo Beige/Pearl Matte Sand Khaki, Metallic Bluish Green

Scan with camera to view videos, key features and more.

[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](#) for full product details.