

2027

KX™ 65



BASE MSRP NON-ABS
\$4,249*



POWER		Rear Tire	80/100-12
Engine	2-stroke, single-cylinder, liquid-cooled	Front Brakes	Single 180mm disc with single-piston caliper
Displacement	64cc	Rear Brakes	Single 180mm disc with single-piston caliper
Bore x Stroke	44.5 x 41.6mm	DETAILS	
Compression Ratio	8.4:1	Frame Type	High-tensile steel semi-double cradle
Fuel System	24mm Mikuni carburetor	Rake/Trail	27.0° / 2.4 in
Ignition	CDI with digital advance	Overall Length	62.6 in
Transmission	6-speed, return shift, with wet multi-disc manual clutch	Overall Width	29.9 in
Final Drive	Chain	Overall Height	37.6 in
PERFORMANCE		Ground Clearance	12.0 in
Front Suspension / Wheel Travel	33mm leading axle telescopic fork with 4-way rebound damping/8.3 in	Seat Height	29.9 in
Rear Suspension / Wheel Travel	Uni-Trak® single shock system with stepless 3-turns rebound damping and fully adjustable spring preload/9.4 in	Curb Weight	126.1 lb* without fuel / 132.2 lb*
Front Tire	60/100-14	Fuel Capacity	1.0 gal
		Wheelbase	44.1 in
		Color Choices	Lime Green

Scan with camera to view videos, key features and more.



*Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.