

2027

MULE PRO-MX™ SE

Kawasaki

Let the Good Times Roll®

BASE MSRP

\$15,899<sup>†</sup>

METALLIC DARK RED



| POWER                           |                                                                               |                              |                                                                                                                                                                                                                                                                                               |
|---------------------------------|-------------------------------------------------------------------------------|------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, single cylinder, SOHC, 4-valve, liquid-cooled                       | Park Brake Type              | Independent, mechanical disc                                                                                                                                                                                                                                                                  |
| Displacement                    | 695cc                                                                         | Ground Clearance             | 10.6 in                                                                                                                                                                                                                                                                                       |
| Maximum Horsepower              | 44.0 hp <sup>1</sup> @ 6,000 rpm                                              | Fuel Capacity                | 9.5 gal                                                                                                                                                                                                                                                                                       |
| Maximum Torque                  | 42.7 lb-ft @ 5,000 rpm                                                        | Turning Radius               | 14.0 ft                                                                                                                                                                                                                                                                                       |
| Bore x Stroke                   | 102.0 x 85.0mm                                                                | Cargo Bed Dimensions (LxWxH) | 33.4 x 44.1 x 9.1 in                                                                                                                                                                                                                                                                          |
| Compression Ratio               | 10.3:1                                                                        | Cargo Bed Load Capacity      | 699 lb / 600 lb CA Model                                                                                                                                                                                                                                                                      |
| Fuel System                     | DFI® with 44mm throttle body                                                  | Payload Capacity             | 1,200 lb / 1,100 lb CA Model                                                                                                                                                                                                                                                                  |
| Transmission                    | Continuously Variable Transmission (CVT) with centrifugal clutch, (H,L,N,R)   | Seating Capacity             | 2                                                                                                                                                                                                                                                                                             |
| Final Drive                     | Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock | Towing Capacity              | 1,500 lb                                                                                                                                                                                                                                                                                      |
| Engine Braking                  | Yes                                                                           | Lighting                     | (2) Halogen headlights, (2) LED headlights                                                                                                                                                                                                                                                    |
| Alternator Output (max)         | 35.7 amp                                                                      |                              |                                                                                                                                                                                                                                                                                               |
| CAPABILITY                      |                                                                               | DETAILS                      |                                                                                                                                                                                                                                                                                               |
| Front Suspension / Wheel Travel | Double wishbone/8.6 in                                                        | Overall Length               | 111.4 in                                                                                                                                                                                                                                                                                      |
| Rear Suspension / Wheel Travel  | Double wishbone/9.1 in                                                        | Overall Width                | 60.0 in                                                                                                                                                                                                                                                                                       |
| Front Tires                     | 25 x 8-12, radial                                                             | Overall Height               | 75.8 in                                                                                                                                                                                                                                                                                       |
| Rear Tires                      | 25 x 10-12, radial                                                            | Estimated Dry Weight         | 1,550.1 lb** / 1,552.3 lb** CA Model                                                                                                                                                                                                                                                          |
| Steering                        | Electric Power Steering (EPS), Tilt steering                                  | Curb Weight                  | 1,622.9 lb* / 1,625.1 lb* CA Model                                                                                                                                                                                                                                                            |
| Front Brakes                    | Dual disc, 2-piston caliper                                                   | Wheelbase                    | 78.9 in                                                                                                                                                                                                                                                                                       |
| Rear Brakes                     | Dual disc, 1-piston caliper                                                   | Instruments                  | Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder lamps |
|                                 |                                                                               | Additional Features          | Roof, WARN® VRX 35 Winch, Cast Aluminum Wheels, Painted Body Panels                                                                                                                                                                                                                           |
|                                 |                                                                               | Color Choices                | Metallic Dark Red                                                                                                                                                                                                                                                                             |

Scan with camera to view videos, key features and more.

<sup>†</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.