

UPDATED 2027

NINJA® 650 ABS



BASE MSRP ABS
\$8,099[†]



LIME GREEN
BASE MSRP \$8,299[†] ABS



METALLIC FLAT SPARK BLACK/METALLIC CARBON GRAY
BASE MSRP \$8,099[†] ABS



METALLIC MATTE TWILIGHT BLUE/CANDY PERSIMMON RED
BASE MSRP \$8,299[†] ABS



GALAXY SILVER
BASE MSRP \$8,299[†] ABS

POWER	
Engine	4-stroke, Parallel Twin, DOHC, liquid-cooled
Displacement	649cc
Bore x Stroke	83.0 x 60.0mm
Compression Ratio	10.8:1
Maximum Horsepower	67.0 hp ¹ @ 8,000 rpm
Maximum Torque	48.5 lb-ft @ 6,700 rpm
Fuel System	DFI® with dual 36mm Keihin throttle bodies
Ignition	TCBI with Electronic Advance
Transmission	6-speed
Final Drive	Sealed chain
Electronic Rider Aids	Economical Riding Indicator, Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Kawasaki Quick Shifter (KQS) available as an accessory

Rear Tire	160/60 x 17
Front Brakes	Dual semi-floating 300mm discs with radial-mounted 4-piston calipers and ABS
Rear Brakes	Single 220mm disc with single-piston caliper and ABS

DETAILS	
Frame Type	Trellis, high-tensile steel
Rake/Trail	24.0° / 3.9 in
Overall Length	80.5 in
Overall Width	29.1 in
Overall Height	44.9 in
Ground Clearance	4.9 in
Seat Height	30.9 in
Estimated Dry Weight	394.7 lb** 50-State Model; 392.5 lb** 49-State Model
Curb Weight	427.8 lb* 50-State Model; 425.6 lb* 49-State Model
Fuel Capacity	4.0 gal
Wheelbase	54.9 in
Special Features	4.3-in all-digital TFT color instrumentation, Smartphone Connectivity with available Voice Command via RIDELOGY THE APP MOTORCYCLE***
Color Choices	Lime Green, Metallic Flat Spark Black/Metallic Carbon Gray, Metallic Matte Twilight Blue/Candy Persimmon Red, Galaxy Silver

PERFORMANCE	
Front Suspension / Wheel Travel	37mm inverted Showa Separate Function Big Piston Fork (SFF-BP)/4.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with adjustable spring preload/5.1 in
Front Tire	120/70 x 17

Scan with camera to view videos, key features and more.



[†]Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.
^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.