

UPDATED 2027

RIDGE® CREW HVAC CAMO



BASE MSRP

\$33,599<sup>+</sup>

TRUETIMBER® STRATA

| POWER                           |                                                            |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|---------------------------------|------------------------------------------------------------|------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled | Fuel Capacity                | 12.9 gal                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Displacement                    | 999cc                                                      | Turning Radius               | 19.0 ft                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Maximum Horsepower              | 116.0 hp <sup>1</sup> @ 8,500 rpm                          | Cargo Bed Dimensions (LxWxH) | 34.6 x 49.0 x 12.8 in                                                                                                                                                                                                                                                                                                                                                                                                              |
| Maximum Torque                  | 73.8 lb-ft @ 8,000 rpm                                     | Cargo Bed Load Capacity      | 1,000/600 lb CA Model                                                                                                                                                                                                                                                                                                                                                                                                              |
| Bore x Stroke                   | 73.4 x 59.0mm                                              | Payload Capacity             | 1,290 lb                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Compression Ratio               | 10.6:1                                                     | Seating Capacity             | 6-person (2 row), bench seats                                                                                                                                                                                                                                                                                                                                                                                                      |
| Fuel System                     | EFI                                                        | Towing Capacity              | 2,500 lb                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Ignition                        | TCBI with Digital Advance                                  | Lighting                     | All-LED lighting                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Starting System                 | Electric                                                   | DETAILS                      |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Transmission                    | Continuously Variable Transmission (CVT) with (H,L,N,R)    | Frame                        | Ladder type, tubular steel                                                                                                                                                                                                                                                                                                                                                                                                         |
| Final Drive                     | Selectable 4WD with locking front/rear differential, shaft | Overall Length               | 156.7 in                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Engine Braking                  | Yes                                                        | Overall Width                | 64.0 in                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Alternator Output (max)         | 85 amp                                                     | Overall Height               | 83.1 in                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Electronic Rider Aids           | Power Modes, Economical Riding Indicator                   | Estimated Dry Weight         | 2,454.2/2,456.4 lb** CA Model                                                                                                                                                                                                                                                                                                                                                                                                      |
| CAPABILITY                      |                                                            | Curb Weight                  | 2,564.4/2,566.6 lb* CA Model                                                                                                                                                                                                                                                                                                                                                                                                       |
| Front Suspension / Wheel Travel | Long-travel, Double wishbone/12.7 in                       | Wheelbase                    | 122.2 in                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Rear Suspension / Wheel Travel  | Long-travel, Double wishbone/12.7 in                       | Instruments                  | Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature) |
| Front Tires                     | SUNF 30 x 10-14                                            | Additional Features          | 4,500-lb winch with synthetic rope, Flip-up windshield, Full Cab with HVAC, Adjustable driver's seat, Front stabilizer bar, ERGO-FIT®, 8-in full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible                                                                                                                                                        |
| Rear Tires                      | SUNF 30 x 10-14                                            | Color Choices                | TRUETIMBER® STRATA                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Wheel Type                      | 14" Aluminum                                               |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Steering                        | Rack-and-pinion w/ Electric Power Steering (EPS)           |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Front Brakes                    | Dual hydraulic 249mm discs with two-piston calipers        |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Rear Brakes                     | Dual hydraulic 249mm discs with single-piston calipers     |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Ground Clearance                | 14.4/15.2 in (max preload); 14.4 in CA Model               |                              |                                                                                                                                                                                                                                                                                                                                                                                                                                    |

Scan with camera to view videos, key features and more.

<sup>+</sup>Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

<sup>\*</sup>Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>\*\*</sup>Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

™/® & © 2026 TrueTimber Outdoors Holding Company, LLC. Manufactured and/or distributed under official license by Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.