

NEW 2027

RIDGE® CREW LIFTED EDITION

Kawasaki

Let the Good Times Roll®



BASE MSRP

\$28,799*

SUNBEAM RED/SUPER BLACK

POWER		Turning Radius	19.0 ft
Engine	4-stroke, DOHC, 4-valve, in-line 4-cylinder, liquid-cooled	Cargo Bed Dimensions (LxWxH)	27.6 x 41.5 x 12.2 in
Displacement	999cc	Cargo Bed Load Capacity	1,000/600 lb CA Model
Maximum Horsepower	116.0 hp ¹ @ 8,500 rpm	Payload Capacity	1,559 lb
Maximum Torque	73.8 lb-ft @ 8,000 rpm	Seating Capacity	6-person (2 row), bench seats
Bore x Stroke	73.4 x 59.0mm	Towing Capacity	2,500 lb
Compression Ratio	10.6:1	Lighting	All-LED lighting
Fuel System	EFI	DETAILS	
Ignition	TCBI with Digital Advance	Frame	Ladder type, tubular steel
Starting System	Electric	Overall Length	156.3 in
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)	Overall Width	64.0 in
Final Drive	Selectable 4WD with locking front/rear differential, shaft	Overall Height	82.9 in
Engine Braking	Yes	Estimated Dry Weight	2,282.2/2,284.4 lb** CA Model
Alternator Output (max)	85 amp	Curb Weight	2,392.4/2,394.6 lb* CA Model
Electronic Rider Aids	Power Modes, Economical Riding Indicator	Wheelbase	121.7 in
CAPABILITY		Instruments	Digital speedometer, tachometer, fuel gauge, odometer, dual trip meters, total time, trip time, average speed, gear indicator, Driving Mode, Power Mode, clock, water temperature, battery voltage, oil change reminder, Bluetooth indicator, Economical Riding Indicator, maintenance reminder, high beam, neutral, reverse, and warning lights (battery, EPS, CVT, seatbelt, parking indicator, oil pressure, water temperature)
Front Suspension / Wheel Travel	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in	Wheel Type	14" Aluminum
Rear Suspension / Wheel Travel	Long-travel, Double wishbone, KYB shocks with piggyback reservoir, adjustable preload and compression damping/12.7 in	Additional Features	Elevated snorkel intakes and CVT exhaust duct, Raised fender flares, Brush guards, Cargo bed storage compartments, High-Density Polyethylene (HDPE) skid plates w/ drain holes, Rear view mirror, 4,500-lb winch with synthetic rope, Adjustable driver's seat, ERGO-FIT®, 8-in full-color TFT Instrumentation with Smartphone Connectivity via RIDELOGY THE APP Powersports, USB ports, KQR™ system compatible
Front Tires	ITP Cryptid 30 x 10-14	Color Choices	Sunbeam Red/Super Black
Rear Tires	ITP Cryptid 30 x 10-14		
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)		
Front Brakes	Dual hydraulic 249mm discs with two-piston calipers		
Rear Brakes	Dual hydraulic 249mm discs with single-piston calipers		
Ground Clearance	14.2/14.6 in (max preload); 14.2 in CA Model		
Fuel Capacity	12.9 gal		

Scan with camera to view videos, key features and more.

^{*}Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

Specifications subject to change. Visit [Kawasaki.com](#) for full product details.