

2027

VERSYS® 650 LT ABS

Kawasaki

Let the Good Times Roll®



BASE MSRP ABS

\$10,599*

 METALLIC CARBON GRAY/METALLIC SPARK BLACK

POWER		Front Brakes	Dual 300mm petal-style discs with 2-piston calipers and ABS
Engine	4-stroke, 2-cylinder, DOHC, 8 valves, liquid-cooled	Rear Brakes	Single 250mm petal-style disc with single-piston caliper and ABS
Displacement	649cc	DETAILS	
Bore x Stroke	83.0 x 60.0mm	Frame Type	Double pipe diamond frame constructed from high-tensile steel
Compression Ratio	10.8:1	Rake/Trail	25° /4.3 in
Maximum Horsepower	66.0 hp ¹ @ 8,500 rpm	Overall Length	85.2 in
Maximum Torque	45.0 lb-ft @ 7,000 rpm	Overall Width	33.1 in
Fuel System	DFI® with 38mm Keihin throttle bodies (2)	Overall Height	53.5 in/55.9 in (windscreen down/up)
Ignition	TCBI with Electronic Advance	Ground Clearance	6.7 in
Transmission	6-speed with positive neutral finder	Seat Height	33.3 in
Final Drive	Sealed chain	Estimated Dry Weight	444.1 lb** (+ approx. 20 lb** w/ saddlebags & hand guards)
Electronic Rider Aids	Kawasaki TRaction Control (KTRC), Anti-lock Brake System (ABS), Economical Riding Indicator	Curb Weight	482.9 lb* (+ approx. 20 lb* w/ saddlebags & hand guards)
PERFORMANCE		Fuel Capacity	5.5 gal
Front Suspension / Wheel Travel	41mm telescopic fork with stepless adjustable rebound and spring preload/5.9 in	Wheelbase	55.7 in
Rear Suspension / Wheel Travel	Single offset laydown shock with remote adjustable spring preload/5.7 in	Special Features	TFT color instrumentation with Smartphone Connectivity via RIDELOGY THE APP MOTORCYCLE, Adjustable windscreen, Hand guards, Clean-mount hard saddlebag system featuring QQR™ mounts
Front Tire	120/70 ZR-17	Color Choices	Metallic Carbon Gray/Metallic Spark Black
Rear Tire	160/60 ZR-17		

Scan with camera to view videos, key features and more.



*Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.