

2027

VULCAN® S ABS



- BASE MSRP ABS
\$8,099⁺
- METALLIC CARBON GRAY/METALLIC BLUISH GREEN
BASE MSRP \$8,299⁺ ABS
- METALLIC FLAT SPARK BLACK
BASE MSRP \$8,099⁺ ABS

POWER		Front Tire	120/70-18
Engine	4-stroke, 2-cylinder, DOHC, liquid-cooled	Rear Tire	160/60-17
Displacement	649cc	Front Brakes	Single 300mm disc with 2-piston caliper and ABS
Bore x Stroke	83.0 x 60.0mm	Rear Brakes	Single 250mm disc with single-piston caliper and ABS
Compression Ratio	10.8:1	DETAILS	
Maximum Horsepower	60 hp ¹ @ 7,500 rpm		
Maximum Torque	46.5 lb-ft @ 6,600 rpm		
Fuel System	DFI® with 38mm throttle bodies (2), with sub-throttle valves		
Ignition	TCBI with Electronic Advance		
Transmission	6-speed with positive neutral finder		
Final Drive	Sealed chain		
Electronic Rider Aids	Economical Riding Indicator, Anti-lock Brake System (ABS)		
PERFORMANCE		Frame Type	High-tensile steel diamond frame
Front Suspension / Wheel Travel	41mm telescopic fork/5.1 in	Rake/Trail	31° /4.7 in
Rear Suspension / Wheel Travel	Lay-down offset rear shock with linkage and adjustable preload/3.2 in	Overall Length	90.9 in
		Overall Width	34.6 in
		Overall Height	43.3 in
		Ground Clearance	5.1 in
		Seat Height	27.8 in
		Estimated Dry Weight	467.5 lb** (ABS), 460.8 lb** (non-ABS)
		Curb Weight	498.3 lb* (ABS), 491.7 lb* (non-ABS)
		Fuel Capacity	3.7 gal
		Wheelbase	62.0 in
		Special Features	ERGO-FIT®
		Color Choices	Metallic Carbon Gray/Metallic Bluish Green, Metallic Flat Spark Black

Scan with camera to view videos, key features and more.

¹Base MSRP is the base for the series of a model and excludes destination, options, taxes, title and license, and dealer fees and charges. Dealer sets actual retail price.

^{*}Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

^{**}Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

¹This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.