

2022

NINJA® ZX™-10R

Kawasaki
 Let the Good Times Roll®

 MSRP NON-ABS
\$17,199

 MSRP ABS
\$18,199

 METALLIC MATTE GRAPHENESTEEL GRAY/
 METALLIC DIABLO BLACK


POWER

Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled
Displacement	998cc
Bore x Stroke	76.0 x 55.0mm
Compression Ratio	13.0:1
Fuel System	DFI® w/47mm Mikuni throttle bodies (4) with oval sub-throttles, two injectors per cylinder
Ignition	TCBI with digital advance and Sport-Kawasaki Traction Control (S-KTRC)
Transmission	6-speed, return shift
Final Drive	Sealed chain
Electronic Rider Aids	Electronic Cruise Control, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Sport Traction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)

PERFORMANCE

Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas-charged shock, stepless, dual-range (low-/high-speed) compression damping, stepless rebound damping, fully adjustable spring preload/4.5 in

Front Tire	120/70 ZR17
Rear Tire	190/55 ZR17
Front Brakes	Intelligent Braking (KIBS) (ABS only), Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers
Rear Brakes	KIBS-controlled (ABS only), single 220mm disc with aluminum single-piston caliper

DETAILS

Frame Type	Aluminum perimeter
Rake/Trail	25.0° / 4.2 in. (ABS); 25.0° / 4.1 in. (non-ABS)
Overall Length	82.1 in.
Overall Width	29.5 in.
Overall Height	46.7 in.
Ground Clearance	5.3 in.
Seat Height	32.9 in.
Curb Weight	456.4 lb*
Fuel Capacity	4.5 gal
Wheelbase	57.1 in.
Special Features	Aerodynamic Downforce Generating Devices, Rideology the App Smartphone Connectivity, TFT Instrumentation
Color Choices	Metallic Matte Graphenesteel Gray/Metallic Diablo Black

 Scan with camera
 to view videos,
 key features
 and more.


*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.