## **MULE PRO-DXT™ DIESEL**





\$14,399



SUPER BLACK



## **POWER**

**Engine** 4-stroke, 3-cylinder, OHV, liquid-cooled, diesel

Displacement

38.3 lb-ft @ 2400 rpm **Maximum Torque** 

Bore x Stroke 2.91x3.03 in

**Compression Ratio** 23.5:1

**Fuel System** Bosch in-line injection pump

Continuously Variable Transmission (CVT) with (H,L,N,R) Transmission

Selectable 2WD/4WD, shaft. Dual mode rear differential **Final Drive** 

with differential lock

**Engine Braking** 

**Alternator Output** 55 amp

(max)

**Ground Clearance** 10.2 in **Fuel Capacity** 7.9 gal

**Turning Radius** 16.0 ft

Cargo Bed 42.7 x 53.7 x 11.0 in (3-person)22.0 x 53.7 x 11.0 in (6-person) **Dimensions (LxWxH)** 

**Cargo Bed Load** 

Capacity

1000 lb (3-person)350 lb (6-person)

**Payload Capacity** 1581 lb

**Seating Capacity** 3-person (1 row), 6 person (2 row)

**Towing Capacity** 

Lighting (2) Halogen headlights.

## CAPABILITY

Front Suspension / Double wishbone / 8.7 in **Wheel Travel** 

Rear Suspension / Wheel Travel

Double wishbone/8.5 (L) /8.7 (R) in

**Front Tires** 26x9.00-12

26x11.00-12

Steering

Rack-and-pinion, Tilt steering

**Front Brakes Rear Brakes** 

**Rear Tires** 

Dual Disc, 2 piston caliper

**Park Brake Type** 

Dual Disc, 1 piston caliper

Independent, Mechanical Disc

**DETAILS Overall Length** 

133.3 in

**Overall Width** 64.0 in

**Overall Height** 77.6 in

**Curb Weight** 1922.8 lb\*

Wheelbase 92.3 in

Instruments

Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters,

2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, glow plug indicator, CVT warning indicator, neutral, reverse and parking indicators,

seatbelt reminder lamps

Wheel Type Steel

**Color Choices** Super Black

Kawasaki Strong 3-Year Limited Warranty Warranty

**Kawasaki Protection** 12, 24, or 36 months Plus™ (optional)

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). All MULE™ PRO Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of ISO 3471

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE™ side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.