

2022

NINJA H2®R

Kawasaki
Let the Good Times Roll®



MSRP
\$56,500

 MIRROR COATED MATTE SPARK BLACK



POWER		REAR TIRE	
Engine	Liquid -cooled, 4-stroke, In-Line Four, DOHC, 16-valve	Front Brakes	190/65 17 Bridgestone Racing Battlax V01R Slick, Medium
Displacement	998cc	Rear Brakes	Dual radial-mount, opposed 4-piston Brembo Stylema® calipers, dual semi-floating 330mm discs, KIBS ABS
Bore x Stroke	76.0 x 55.0mm		Opposed 2-piston calipers, single 250mm disc, KIBS ABS
Compression Ratio	8.3:1	DETAILS	
Maximum Torque	121.5 lb-ft @ 12,500 rpm	Frame Type	Trellis, high-tensile steel, with swingarm mounting plate
Fuel System	DFI® with 50mm throttle bodies (4) with dual injection ; Kawasaki Supercharger	Rake/Trail	25.1° /4.3 in
Ignition	Digital	Overall Length	81.5 in
Transmission	6-speed, return, dog-ring	Overall Width	33.5 in
Final Drive	Sealed chain	Overall Height	45.7 in
Electronic Rider Aids	Kawasaki Cornering Management Function (KCMF), Kawasaki TRaction Control (KTRC), Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS), Kawasaki Engine Brake Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Öhlins Electronic Steering Damper	Ground Clearance	5.1 in
PERFORMANCE		Seat Height	32.7 in
Front Suspension / Wheel Travel	43mm inverted fork with adjustable rebound and compression damping, spring preload adjustability and top-out springs/4.7 in	Curb Weight	476.3 lb*
Rear Suspension / Wheel Travel	Uni-Trak®, Öhlins TTX36 gas charged shock with piggyback reservoir, 30-way compression and rebound damping and adjustability, and 16-way spring preload adjustability and top-out spring/5.3 in	Fuel Capacity	4.5 gal
Front Tire	120/60 ZR17 V01F slick	Wheelbase	57.1 in
		Special Features	Aerodynamic downforce generating devices, Highly Durable Paint, Analog Tach & LCD instrumentation
		Color Choices	Mirror Coated Matte Spark Black
		Warranty	N/A
		Kawasaki Protection Plus™ (optional)	N/A

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit [Kawasaki.com](https://www.kawasaki.com) for full product details.