²⁰²⁴ **KLX®140R F**







POWER		Front Brakes	Single 220mm petal disc with a dual-piston caliper
Engine	4-stroke single, SOHC, air-cooled	Rear Brakes	Single 186mm petal disc with single-piston caliper
Displacement	144cc		
Bore x Stroke	58.0 x 54.4mm	DETAILS	
Compression Ratio	9.5:1	Frame Type	High-tensile steel, box-section perimeter
Fuel System	20mm Keihin carburetor	Rake/Trail	27°/4.6 in
Ignition	Digital DC-CDI	Overall Length	78.9 in
Transmission	5-speed, return shift, with wet multi-disc	Overall Width	31.1 in
	manual clutch	Overall Height	44.7 in
Final Drive	Chain	Ground Clearance	12.4 in
PERFORMANCE		Seat Height	33.9 in
Front	33mm telescopic fork/7.5 in	Curb Weight	218.2 lb*
Suspension / Wheel Travel		Fuel Capacity	1.5 gal
Rear	Uni-Trak® linkage system and single shock	Wheelbase	52.4 in
Suspension / Wheel Travel	with piggyback reservoir, 20-way rebound damping and threaded preload	Color Choices	Lime Green, Battle Gray
	adjustability/7.9 in	Warranty	6 Month Limited Warranty
Front Tire Rear Tire	2.75 x 21 4.10 x 18	Kawasaki Protection Plus™ (optional)	12, 24, or 36 months



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2024 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.